

Oil Suction & Discharge Hoses

10 Bar W.P 150 PSI



Application

10 Bar (150 PSI) light weight (50% aromatics) suction and delivery of petroleum products.

Type: Mandrel-Built Hose

Tube: Black color or NBR blend (50% aromatics) with static conducting

Finishing: Wrapped Surface

Reinforcement: Multi layers nylon cord with high tensile steel wire.

Cover : Black Oil and Weather, It is resistant to ozone crack, abrasion and weather condition.

Temperature Range: -35°C to 100°C (30°F to 212°F)

Part No	ID x OD		Max. Work Pressure	Burst Pressure	Standard Length	Weight
	Inch	MM	PSI	PSI	M	KG / M
IF611-16	1.00 x 1.42	25 x 36	150	450	60	1.01
IF611-20	1.25 x 1.69	32 x 43	150	450	60	1.22
IF611-22	1.38 x 1.81	35 x 46	150	450	60	1.18
IF611-24	1.50 x 1.93	38 X 49	150	450	60	1.41
IF611-26	1.57 x 2.08	40 x 53	150	450	60	1.64
IF611-32	2.00 x 2.50	51 x 63	150	450	60	1.93
IF611-40	2.50 x 3.03	63 x 77	150	450	60	2.35
IF611-48	3.00 x 3.54	76 x 90	150	450	60	2.89
IF611-64	4.00 x 4.65	102 x 118	150	450	60	4.21
IF611-80	5.00 x 5.71	127 x 145	150	450	40	5.65
IF611-96	6.00 x 6.73	152 x 171	150	450	30	6.98
IF611-128	8.00 x 8.86	203 x 225	150	450	12/30	12.64
IF611-160	10.00 x 11.02	254 x 280	150	450	12	29
IF611-192	12.00 x 13.00	305 x 330	150	450	12	49

For more details or product related enquires feel free mail us: info@italflexitaly.it