


Water Suction & Discharge Hoses 10 Bar W.P 150 PSI



Application

10 Bar (150 PSI) heavy duty water suction delivery hose

Type : - Mandrel-Built Hose

Finishing: - Wrapped Surface

Cover :Black Colour of EPDM blend, It is resistant to ozone crack, abrasion and weather condition.

Reinforcement:High tensile wire helix embedded between layers of Nylon Cord.

Tube:Black NR/SBR rubber Compound hose for water

Temperature Range:-35°C to 80°C (30°F to 180°F)

Part No	ID x OD	ID x OD	Max. Work Pressure	Burst Pressure	Standard Length	Weight
	Inch	Inch	PSI	PSI	M	KG / M
IF601-12	0.75 x 1.18	19 x 30	150	450	60	0.7
IF601-16	1.00 x 1.42	25 x 36	150	450	60	0.9
IF601-20	1.25 x 1.69	32 x 43	150	450	60	1.1
IF601-24	1.50 x 1.93	38 x 49	150	450	60	1.26
IF601-32	2.00 x 2.50	51 x 63	150	450	60	1.75
IF601-40	2.50 x 3.03	63 x 77	150	450	60	2.13
IF601-48	3.00 x 3.54	76 x 90	150	450	60	2.73
IF601-64	4.00 x 4.65	102 x 116	150	450	30	3.75
IF601-80	5.00 x 5.67	127 x 144	150	450	30	5.05
IF601-96	6.00 x 6.73	152 x 171	150	450	30	6.59
IF601-128	8.00 x 8.86	203 x 225	150	450	12/30	12.12
IF601-160	10.00 x 11.02	254 x 280	150	450	12	16.11
IF601-192	12.00 x 13.00	305 x 330	150	450	12	22.39

For more details or product related enquires feel free mail us: info@italflexitaly.it